

Bush Hog® TOUGH

Commercial Series Zero Turn Mowers

BUSH HOG® TOUGH FEATURES

TOUGH Commercial Grade Spindles Greased From The Top

TOUGH 7 Gauge Or 10 Gauge Welded Steel Decks

TOUGH Rolled Front Edge Deck With 3/8 Inch Bar For Extra Protection

TOUGH Fully Floating Deck

TOUGH Durable Anti-Scalp Rollers

TOUGH Long Lasting Electric Clutches



MODELS	Engines and Decks	Width x Length (deflector down)	Dry Weight* (*lbs. with standard seat)
CZ2149	21 HP Kawasaki®/49 inch deck	61 x 82	1,230
CZ2349	23 HP Kohler® Command™ Pro/49 inch deck	61 x 82	1,230
CZ2355	23 HP Kohler® Command™ Pro/55 inch deck	67 x 82	1,270
CZ2555	25 HP Kawasaki® FH72IV/55 inch deck	67 x 82	1,270
CZ2561	25 HP Kawasaki® FH72IV/61 inch deck	73 x 85	1,295

VEHICLE	
Drive System	Dual Hydro-Gear® variable displacement pumps and high efficiency Hydro-Gear® motors. 1.0 gallon reservoir. Cooling fans with each pump.
Brakes	Hydro provides dynamic braking; disc-type parking brake
Electrical System	12 volt, Rated at 230 CCA; electric start
Steering/Motor Control	Dampened twin levers, adjustable fore and aft and vertically
Front Caster Tires	13 x 5.0-6 4 ply tubeless on 49 inch and 55 inch decks 13 x 6.5-6 4 ply tubeless on 61 inch decks
Drive Tires	23 x 8.5-12 4 ply on 49 inch decks 24 x 9.5-12 4 ply on 55 inch decks 24 x 12-12 4 ply on 61 inch decks
Speed	Infinitely variable; 0-10 MPH forward
PTO Engagement	Mag Stop™ Electromagnetic clutch rated at 175 ft lbs
Fuel Capacity	12.5 gallons; twin fuel tanks
Seat Options	High-back, foam padded seat with flip-up arm rests and seat slides High-back full suspension seat with flip-up arm rests and seat slides
Features/Gauges	Tachometer/hour meter, low engine oil pressure warning light, low engine oil pressure audible alert, high engine temperature warning light and audible alert for Kohler® models, molded-in beverage holder, molded-in storage, large vented fuel caps and fuel tank Sitalines
Safety	Operator presence controls (OPC), Certified fold-down ROPS with seatbelt
Controls	Key ignition, throttle, choke, PTO switch, park brake lever

DECKS	
Style	7 gauge steel on 55 inch and 61 inch, 10 gauge steel on 49 inch, fully floating, 51/2 inch deep side discharge
Deck lift	Quick Foot™ height adjustment from the seat
Blades	1/4 inch thick, heat-treated high alloy steel, High Lift SM
Cutting Height Range	1 1/2 to 5 inches, adjustable in 1/4 inch increments
Blade Tip Speed	18,500 FPM
Accessories	Grass Mulching Kits, Stripping Roller, Canopy, Working Lights, Trailer Hitch Kit, Max Vac Grass Collection System and Bar tires.

WARRANTY	
	3 year limited warranty (third year parts only) includes drive train, electromagnetic clutch, deck and cutter spindles. See dealer for complete details. Engine warranty administered through engine manufacturer.